



DECLARATION OF PERFORMANCE
according to Annex III of the EU-regulation No. 305/2011
(construction products regulation)

No. OWA-00006.1.1

1. Unique identification code of the product-type:

T006-Mineral tiles-A2_s1_d0

2. Intended use:

Suspended ceilings

3. Manufacturer:

OWA Odenwald Faserplattenwerk GmbH
Dr.-F.-A.-Freundt-Straße 3
63916 Amorbach
Germany
Phone: +49 (0)9373/2010, Email: info@owa.de
Internet: www.owa-ceilings.com

4. Authorised representative:

Managing Director MBA Maximilian von Funck
Managing Director Dipl.-Wirtsch.-Ing. Jürgen Theobald
OWA Odenwald Faserplattenwerk GmbH
Dr.-F.-A.-Freundt-Straße 3
63916 Amorbach
Germany
Phone: +49 (0)9373/2010, Email: info@owa.de
Internet: www.owa-ceilings.com

5. Systems of AVCP:

System 3, System 4

6a. Harmonised standard:

EN 13964:2014

Notified body:

NB 0672

Odenwald Faserplattenwerk GmbH | Dr.-F.-A.-Freundt-Straße 3 | 63916 Amorbach | Germany | tel +49 9373 201-0 | fax +49 9373 201-130 | info@owa.de
Registered office: 63916 Amorbach | Register court: HRB 131 Aschaffenburg | USt.-IdNr. DE132096747 | Tax number 204/118/81149 | EORI No. DE 2241854
Managing Directors: MBA Maximilian von Funck | Dipl.-Wirtsch.-Ing. Jürgen Theobald

Deutsche Bank Aschaffenburg | BIC: DEUTDEFF795
IBAN: DE11 7957 0051 0023 2355 00

HypoVereinsbank Aschaffenburg | BIC: HYVEDEMM407
IBAN: DE11 7952 0070 0001 6880 30

Sparkasse Miltenberg-Obernburg | BIC: BYLADEM1MIL
IBAN: DE86 7965 0000 0620 3011 01

7. Declared performances:

Mineral tiles according to EN 13964:2014		
Essential characteristics	Declared performance	Harmonised technical specification
Reaction to fire	A2-s1,d0	EN 13964:2014 EN 13501-1:2019-05
Release of asbestos	no content	EN 13964:2014
Release of formaldehyde	E1	EN 13964:2014
Release of dangerous substances	no release	EN 13964:2014
Susceptibility to the growth of harmful micro-organisms (Dampness, Thermal insulation)	no performance determined	EN 13964:2014
Bond strength/ adhesion	no performance determined	EN 13964:2014
Shatter properties	no performance determined	EN 13964:2014
Flexural tensile strength	annex 1	EN 13964:2014
Sound absorption	annex 1	EN 13964:2014
Thermal conductivity	no performance determined	EN 13964:2014
Durability	C	EN 13964:2014

8. The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

All Declarations of performance are available on website <http://www.owa-ceilings.com>.

Amorbach, May-23



i.V. Dr. Holger Kindermann
Head of PD



i.V. André Overbeck
OWAconsult, Dipl. -Ing. (TU)

Annex 1

OWAconsult collection	α_w-value	Flexural tensile strength N/m²
Curve* ²	1,00	no performance determined
FreeStyle Lamellen/ baffles* ²	0,60	no performance determined
FreeStyle Wandabsorber/ wallabsorber* ²	0,90	no performance determined
OWAplan ⁷⁰ inkl. Putzbeschichtung/ incl. plaster coating* ¹	0,65	C/556
OWAplan ⁹⁰ inkl. Putzbeschichtung/ incl. plaster coating* ¹	0,90	C/556
Selecta* ²	1,00	no performance determined

¹ The absorption properties refer to OWAplan S white and OWAplan XS white and depend on the mineral board used.
There may be a minimal reduction in acoustic absorption for OWAplan color depending on the respective colour shade.

² fleece